

PM790

DMR Mobile Radio

-
- Digital and Analogue Compatible
 - Multiple External Interfaces
 - Excellent Ergonomics
 - Loud and Clear Audio
 - Multi-Featured
 - IP54
-



Technical Specifications

General	
Digital Protocol	ETSI TS102 361-1,-2,-3,-4
Frequency	UHF1:400-470MHz VHF: 136-174MHz
Channel Capacity	1024
Zone Capacity	64
Channel Spacing	12.5KHz/20KHz/25KHz
Frequency Stability	±0.5ppm
Operating Voltage	DC13.6V ± 15%
Size (HxWxD)	49x178x156mm
Weight	About 1.4Kg
Screen	2.0" TFT LCD, 220x176, 4 Lines Text
Vocoder	AMBE++
Bluetooth	Support BT2.1+EDR/4.0
Location	GPS/Glonass
Encryption	Support SW and HW Encryption(Optional)
Receiver	
Sensitivity (Analogue)	0.3uV (12dB SINAD)
Sensitivity (Digital)	0.3uV (5% BER)
Adjacent Channel Selectivity	60 dB @ 12.5KHz / 70 dB @ 20 / 25KHz (TIA603A) -1T
	50 dB @ 12.5KHz / 75 dB @ 20 / 25KHz (TIA603D) -2T
	60 dB @ 12.5KHz / 70 dB @ 20 / 25KHz (ETSI)
Intermodulation	75 dB (TIA603D)
	70 dB (ETSI)
Spurious Rejection	75 dB (TIA603D)
	70 dB (ETSI)
Blocking or desensitization	90 dB(TIA603D)
	84 dB(ETSI)
Co-channel rejection	-12~0 dB @ 12.5KHz / -8~0 dB @ 20 / 25KHz
Hum and Noise	-40 dB @ 12.5KHz / -43dB @ 20KHz / -45 dB @ 25KHz
Rated Audio Power	3W (Internal)
Max Audio Power	6W (Internal)
Audio Distortion @ Rated Audio	≤3% (Typical)
Audio Response	+1~-3dB(TIA603D)
Conducted Spurious Emission	-57 dBm (TIA603D)

Transmitter	
Low Power Output	1W-25W (UHF3) / 5-25W(UHF1 / VHF)
High Power Output	5-45W (UHF1/UHF3) / 5-50W (VHF)
FM Modulation	12.5KHz: 11K0F3E / 20KHz: 14K0F3E / 25KHz: 16K0F3E
	12.5KHz Data Only: 7K60F1D&7K60FXD
4FSK Digital Modulation	12.5KHz Voice Only: 7K60F1E&7K60FXE
	12.5KHz Voice and Data: 7K60F1W
Conducted/Radiated Emission	-36dBm ≤1GHz ; -30dBm >1GHz
Modulation Limiting	±2.5KHz @ 12.5KHz / ±4KHz @ 20KHz / ±5.0KHz @ 25KHz
FM Hum and Noise	-40 dB @ 12.5KHz / -43dB @ 20KHz / -45 dB @ 25KHz
Adjacent Channel Power	60 dB @ 12.5KHz / 70 dB @ 20 / 25KHz
Audio Distortion	≤3%(Typical)
Audio Response	+1~-3dB(TIA603D)
Environmental	
Operating Temperature	-30°C ~ +60°C
Storage Temperature	-40°C ~ +85°C
ESD	IEC 61000-4-2 (level 4) ±8kV (Contact) ±15kV(Air)
Dust and Water Resistance	IP54
Thermal Shock	MIL - STD - 810 G
GPS	
Accuracy specs are for long-term tracking (95th percentile values>5 satellites visible at nominal -130 dBm signal strength)	
TTF (Time To First Fix) - Cold Start	<60s
TTF (Time To First Fix) - Hot Start	<10s
Horizontal Accuracy	<10m

Standard Accessories

	
Mounting Bracket	GPS Antenna
	
Full Keypad Microphone	DC Power Cable



Website: www.caltta.co.uk

Address:12F/Building G2, International E-City, Nanshan, Shenzhen, China, 518052

General Disclaimer:

The specifications in this document are in accordance with the applicable standard test. Due to the continuous technology development, Caltta may change the specifications without notice.

Authorised UK Partner

TRONEX
TELECOMMUNICATIONS LTD